

300 Series Air Couplers "Aro 210"




Introduction

The 300 series is the ideal choice when a tough, durable product of superior quality is required.

Features

- ◆ Single hand operation
- ◆ Light weight
- ◆ Large flow valve
- ◆ Interchange: Parker 50 series, ARO 210 & Rectus 22KA



Specification

- ◆ Operating temperature with standard NBR seals -20°C (-20°F) to 120°C (248°F)
- ◆ MWP 232 PSI

Part #	LS	D		A	T	d
300-07SH	69.8	23.3	20	20	7	4
300-09SH	74.8	23.3	20	25	9	5.5
300-11SH	74.8	23.3	20	25	11	7.5

Part #	LS	D		A	T BSPP	d
300-04SF	59.8	23.3	20	13	1/4	14
300-06SF	59.8	23.3	22	12	3/8	14

Part #	LS	D		A	T BSPT	d
300-04SM	62.8	23.3	20	13	1/4	7.8
300-06SM	60.8	23.3	20	13	3/8	11.3

Part #	LP	C		A	T BSPT	d
300-07PM	41	22	14	13	1/4	5.4
300-09PM	41.5	22	17	13	3/8	5.4

Part #	LP	C		A	T BSPT	d
300-04PF	38	22	17	13	1/4	5.4
300-06PF	38	22	19	13	3/8	5.4

Part #	LS	C	CP	A	T	d
300-07PH	44.5	22	15	20	7	5.4
300-09PH	49.5	22	15	25	9	5.4
300-11PH	49.5	22	15	25	11	5.4