Phone: 021 161 0867 Quick Couplers

## Swivels Straight & 90 Deg



Material: Steel

♦ Seals: Nitrile (Buna-N), Viton on Request Wear Ring: Teflon

♦ Working Temperature: NBR –20°C to +100°C Viton –15°C to +180°C

♦ Threads: BSP, NPT by Request





Body Size	Thread		Part #		Material
	Female	Male	Straight	90 Deg	IVIALETIAI
1/4	1/4 BSPP	1/4 BSPP	SJ10-04	SJ90-04	Steel
3/8	3/8 BSPP	3/8 BSPP	SJ10-06	SJ90-06	Steel
1/2	1/2 BSPP	1/2 BSPP	SJ10-08	SJ90-08	Steel
3/4	3/4 BVSPP	3/4 BSPP	SJ10-12	SJ90-12	Steel
1"	1" BSPP	1" BSPP	SJ10-16	SJ90-16	Steel
1 1/4	1 1/4 BSPP	1 1/4 BSPP	SJ10-20	SJ90-20	Steel
1 1/2	1 1/2 BSPP	1 1/2 BSPP	SJ10-24	SJ90-24	Steel
2"	2" BSPP	2" BSPP	SJ10-32	SJ90-32	Steel

## **Rotating System:**

Sizes 1/4, 3/8, 1/2 have a single ball race.

Sizes 3/4 to 2" have a double ball race.

The SJ swivel is the ideal choice for mounting between a rotating hose and a solid mount to extend the life of the hose.

## Caution:

The SJ swivel is not intended to be used in a continuous movement or high speed rotation.

Email: sales@hydconnect.com www.hydconnect.com