onnect

Force to

Connect N

213

215

FFH Series Cartridge


Introduction

The FFH Series is a replacement flat face cartridge coupler to suit the Faster FFI, FI '46 mm' & FFH, FH 48 mm housings. Designed for quick attachment change over for skid steer loaders, compact loaders, track loaders.

Construction

- Carbon steel with trivalent plating
- Seals Nitril Buna-N
- Back up Teflon
- Internal Springs 302 Stainless Steel
- Series Interchange ISO 16028





Part #	Size	Thread	Е	F	G
FFHF-08M46	1/2	M46*1.5	102	42	38
FFHF-08M48	1/2	M48*1.5	103	50	38
FFHF-12M48	3/4	M48*1.5	110	50	48

Hydrauli

Operating temperature with standard NBR

Flow Rate

110

160

seals –20°C (-20°F) to 120°C (248°F)

Specification

Size

1/2

3/4

MWP PSI

5000

5000





Part #	Size	Thread	Α	С	D
FFHM-08M46	1/2	M46*1.5	99	42	24.5
FFHM-08M48	1/2	M48*1.5	100	50	24.5
FFHM-12M48	3/4	M48*1.5	115	50	30

M48 Fits 4BD4FH Block M46 Fits 4BD4FI Blocks