

S75 Series Screw Coupler



Screw to connect couplings for the oil and gas industries, heavy duty applications, market interchange.

Screw to connect coupling popular for use in those heavy duty applications.

Robust design, lug wing nut for easy connection under pressure, poppet valve and ACME connection thread.

Available standard with NPT connection threads.

Applications:

- Heavy mobile machinery
- Oil & Gas applications
- Power generation
- Mining



Body Size			Thread		Working	Flow Rate	Spillage
Inch	Din	Dash	Type	Size	(Bar)	(l/min)	(ml)
1"	25	-16	ACME	1"	350	230	18
1 1/4"	32	-20	ACME	1 1/4"	350	320	21
1 1/2"	38	-24	ACME	1 1/2"	350	330	41

Dust caps and plugs are available

Material	Steel
Seals	NBR
Working Temperature	-25° C to +120° C

Valve Type	Poppet
Connection	Screw to Connect
Connect under Pressure	Allowed Residual

Market Interchange			
Faster	OGV	DNP	VFH1
Stucchi	VOF	Dixon	WS
Parker	75	Snap-Tite	S75
Holmbury	LC	Voswinkel	HV
Eaton	FD85	Hydraulics Inc	5TV

S75 Dust Caps & Plugs		
Size	Cap	Plug
1"	S75DC-16	S75DP-16
1 1/4"	S75DC-20	S75DP-20
1 1/2"	S75DC-24	S75DP-24